

- Α.
- Β. **PVC PIPE WITH FITTINGS**
- LANDSCAPE PRODUCTS 17MM EZ-ID CV COLOR CODED DRIPLINE C.
- 17MM INSERT FITTING (TYPICAL) D.
- FLUSH POINT Ε.
- F. TREE
- G. SHRUB
- Η. ORNAMENTAL

NOTES:

- 1. DISTANCE BETWEEN LATERAL RINGS AND EMITTER SPACING TO BE BASED ON SOIL TYPE, AND TREE CANOPY.
- 2. PLACE TIE DOWN STAKES EVERY 3' IN SAND, 4' IN LOAM, AND 5' IN CLAY.

17MM EZ-ID CV DRIPLINE LAYOUT FOR SPECIMEN PLANTINGS

NOT TO SCALE

LANDSCAPE PRODUCTS VALVE BOX WITH DRIP REMOTE CONTROL ZONE KIT

3. AT FITTINGS WHERE THERE IS A CHANGE OF DIRECTION SUCH AS TEES OR ELBOWS, USE TIE-DOWN STAKES ON EACH LEG OF THE CHANGE OF DIRECTION.

gle Lateral Maximum Run	Length (Feet)
-------------------------	---------------

nlet ssure osi)	12" Spacing			18" Spacing			
	Nominal Flow (gph)			Nominal Flow (gph)			
	0.4	0.6	1.0	0.4	0.6	1.0	
15	220	170	125	285	240	170	
25	326	255	195	495	370	275	
35	410	330	238	572	470	335	
45	474	360	270	640	515	375	