



Polyethylene & PVC Vinyl Tubing



High quality polyethylene (PE) tubing manufactured by Landscape Products is ideal for use in drip irrigation systems for landscapes and agriculture. This tubing can be used to connect any drip or micro device to the water supply lateral or attached to the outlet of a buried emitter to bring water to the surface. It can also be used as a leader to bring water from a buried hose to a surface emitter or micro sprayer.

All PE tubing is made with 100 percent Dow Chemical 7510 material, which has a 30 plus year record of product quality. This material is known for having excellent environmental stress crack resistance (ESCR). A minimum of 2 percent carbon black color protects the tubing from the harmful effects of the sun.



www.landscapeproductsinc.com

For more information or to find a distributor, contact: Landscape Products Inc.

Arizona – 610 S. 80th Ave., Tolleson, AZ 85353
Office: (623) 643-9704 | Fax: (623) 643-9734

Florida – 1045 Garden St., Unit 5, Kissimmee, FL 34744
Office: (407) 932-0900 | Fax: (407) 932-0901



Polyethylene & PVC Vinyl Tubing

| Specifications | | | | | | | |
|----------------|--|-----------|-----------|-----------|-----------------|------------------|------------------------|
| Item Number | Description | I.D. (in) | O.D. (in) | Wall (in) | Weight per Roll | Units per Pallet | Max Operating Pressure |
| 12000995 | LP 185 1/8-Inch x 1,000-Foot Vinyl Tubing | 0.125 | 0.187 | 0.030 | 8.80 lb | 64 | 50 PSI |
| 12000890 | LP 220 1/4-Inch x 100-Foot Vinyl Drip Tubing | 0.160 | 0.220 | 0.030 | 1.20 lb | 720 | 50 PSI |
| 12000900 | LP 220 1/4-Inch x 1,000-Foot Vinyl Tubing | 0.160 | 0.220 | 0.030 | 12.0 lb | 64 | 50 PSI |
| 12000910 | LP 250 1/4-Inch x 100-Foot Vinyl Tubing | 0.170 | 0.250 | 0.040 | 1.80 lb | 720 | 50 PSI |
| 12000915 | LP 250 1/4-Inch x 1,000-Foot Vinyl Tubing | 0.170 | 0.250 | 0.040 | 18.0 lb | 64 | 50 PSI |
| 12000920 | 1/4-Inch x 1,000-Foot PE Tubing | 0.170 | 0.250 | 0.040 | 13.58 lb | 36 | 50 PSI |
| 12000925 | 1/4-Inch x 1,000-Foot PE Tubing Bucket Refill | 0.170 | 0.250 | 0.040 | 11.4 lb | 36 | 50 PSI |
| 12000934 | 1/4-Inch x 1,000-Foot Vinyl Tubing In Bucket | 0.170 | 0.250 | 0.040 | 20.18 lb | 36 | 50 PSI |
| 12000940 | LP 350 1 1/32-Inch x 500-Foot PE Tubing | 0.250 | 0.350 | 0.050 | 10.0 lb | 64 | 50 PSI |
| 12001000 | LP 185 1/8-Inch x 100-Foot PE Tubing | 0.125 | 0.187 | 0.030 | 0.66 lb | 720 | 50 PSI |
| 12001005 | LP 185 1/8-Inch x 1,000-Foot PE Tubing | 0.125 | 0.187 | 0.030 | 6.60 lb | 64 | 50 PSI |
| 12001006 | LP 250 1/4-Inch x 100-Foot PE Tubing | 0.170 | 0.250 | 0.040 | 1.10 lb | 720 | 50 PSI |
| 12001007 | LP 250 1/4-Inch x 1,000-Foot PE Tubing | 0.170 | 0.250 | 0.040 | 11.0 lb | 64 | 50 PSI |
| 12001008 | LP 710 1/2-Inch x 100-Foot PE Tubing | 0.605 | 0.710 | 0.052 | 4.51 lb | 90 | 55 PSI |
| 12001010 | LP 710 1/2-Inch x 500-Foot Red Stripe Drip Tubing | 0.605 | 0.710 | 0.052 | 22.55 lb | 36 | 55 PSI |
| 12001012 | LP 710 1/2-Inch x 500-Foot White Stripe Drip Tubing | 0.605 | 0.710 | 0.052 | 22.55 lb | 36 | 55 PSI |
| 12001014 | LP 710 1/2-Inch x 500-Foot Purple Stripe Drip Tubing | 0.605 | 0.710 | 0.052 | 22.55 lb | 36 | 55 PSI |
| 12001016 | LP 710 1/2-Inch x 500-Foot No Stripe Drip Tubing | 0.605 | 0.710 | 0.052 | 22.55 lb | 36 | 55 PSI |
| 12001018 | LP 940 3/4-Inch x 100-Foot PE Tubing | 0.820 | 0.940 | 0.055 | 6.8 lb | 60 | 52 PSI |
| 12001020 | LP940 3/4-Inch x 500-Foot Drip Tubing | 0.820 | 0.940 | 0.055 | 34.0 lb | 10 | 52 PSI |
| 12001024 | LP 940 3/4-Inch x 500-Foot PE Purple Stripe Tubing | 0.820 | 0.940 | 0.055 | 34.0 lb | 10 | 52 PSI |
| 12001026 | LP 940 3/4-Inch x 500-Foot Black PE Tubing | 0.820 | 0.940 | 0.055 | 34.0 lb | 10 | 52 PSI |
| 12001030 | LP 1200 1-Inch x 500-Foot PE Drip Tubing | 1.060 | 1.200 | 0.070 | 51.0 lb | 10 | 51 PSI |



Landscape Products, Inc. warrants polyethylene tubing and PVC vinyl tubing to be free from original defects in material and workmanship for a period of seven (7) years from the date of manufacture. LPI further warrants any of its polyethylene tubing to be free from environmental stress cracking for a period of fifteen (15) years from the date of manufacture.